



玄云动力
SWIWIN TURBINE

SWIWIN SW300B

Technical specifications



SWIWIN SW300B List of engine accessories

Serial number	Name	Picture specification	Quantity
1	Engine		one
2	ECU (V3)		one
3	GSU		one
4	Fixture		one
5	Brushless fuel pump		one
6	Power cable		one
7	Signal cable		one



8	Throttle cable		one
9	Switch valve		one
10	Filter		one
11	Tubing	 $\Phi 4 \times \Phi 2.5\text{mm}$ $\Phi 6 \times \Phi 4\text{mm}$	1.5m



Technical parameter

Model	SW300B
Thrust	30kg
Diameter (mm)	132mm
Length (mm)	333mm
Weight	2560g
ECU weight	42g
Usage temperature	-40℃~50℃
Supply voltage	3S Lipo battery
Starting system	One-button electronic start
Rpm Range	38000-98000
Exhaust Temperature	750℃
Fuel Consumption	820g/min
Fuel	kerosene
Lube oil	3%~5%
Maintenance Interval	25H



Engine start parameters

Pump Voltage	0.5-1V
RPM Start Up Ramp	100%
Pump Start Up Ramp	3
Glow Plug	5-7V
Valve	40
Ignition RPM	3000
Preheat RPM	4000
RPM Off Starter	16000

Engine operating parameters

RPM ACC	25
RPM DEC	25
Max RPM	98000
Idle RPM	38000
Minimum speed	20000
Max Temp	1000
Low Volt	10V
Restart	close
Restart Glow Plug	Consistent with the voltage of the burner
Pump Limit	13V
Idle Stable	5-8

Engine cooling parameters

Cool	4000rpm
------	---------


Starting motor parameters

Pop-up time	0.4S
Ejection voltage	4V
Run Voltage	5V
RPM Stable	20

Note: All data are measured at standard air pressure.




System connection diagram





Product dimension diagram



Disclaimer

This internal combustion engine is only used for Model RC, Toy aircraft as power source, it can only be used for model airplane flight, model airplane flying show and other entertainment activities. According to the Export control law of the People's Republic of China and the Export control law of the USA. It is strictly forbidden to modify the product for illegal use. It is strictly prohibited to resell the product to the export restriction country under the law in China. Otherwise, all consequences will be at your own risk.